











PAGE 81

PAGE 81

PAGE 81

PAGE 8

	CP512 300	CP512 300i	CP514 350	CP514 350i
Power	4kW - 5,4HP	4kW - 5,4HP	4kW - 5,4HP	4kW - 5,4HP
Max. diameter	Ø 300mm	Ø 300mm	Ø 350mm	Ø 350mm
Easy Start	✓	✓	✓	✓
i-Lube™ separate Iubrification	×	✓	×	✓



HANDHELD CUT-OFF SAWS



CP500s range

FAST ENOUGH TO GET YOU ON AND OFF THE JOB. TOUGH ENOUGH TO LAST.

Norton Clipper introduces a new option for hand held cut-off saws. Raw power for smooth, fast cuts with features that prolong saw life, prevent engine damage and guarantee everyday reliability.

Water-spraying system

Magnesium blade guard, with position adjustment handle

Compact design, powerful 5,4HP engine

20mm arbor, 25,4mm bushing ring included

Electronic carburator -No choke required

EASY START

Multi-stage air filtration with external rocker wheel

Over-tightening protection on tank caps

Back-end handle and enhanced weight balance

Reversing cutting head

V-belt with semiautomatic tensionning

> 5-springs anti-vibration system



iLube[®] version only: separate oil tank - no more premixing of oil and fuel

KEY FEATURES

USER-FRIENDLY

- 4kW / 5,4HP powerful motor.
- Electronic carburator allows an easy 3-step en gine start. No more choke or half-throttle set-up.
- Easy stopping: just press the red button!
- 5-spring anti-vibration system.
- Back-end handle and enhanced weight balance.
- iLube®: No more worrying about 2-stroke fuel mixtures. Just fill with regular fuel and 2-stroke oil!

LONG-LIFE and LOW MAINTENANCE

- · Easy semi-automatic belt tensioning.
- Multi-Stage Air Filter with pulsating air streams. Fitted with external rocker wheel to keep the filters from clogging.
- Magnesium blade guard for extra safety and lighter weight.
- Nikasil-coated cylinder and heavy duty starter rope for longer life.
- V-belt for driving cutting blade.
- Tank caps with over-tightenting protection.





No More Pre-Mixing Oil & Fuel *



AUTOMATIC MIX ™:

Fill oil and fuel tanks separately.
The internal oil pump and sensor mix them perfectly for enhanced longevity.

Save fuel costs through buying fuel and oil separately instead of expensive pre-mix.

Fill in the 2 distinct tanks and the patented iLube® system will automatically mix oil and fuel for maximum efficiency and prevent damage.

Save maintenance costs with iLube® system. No more damage from overheating from forgetting oil, or piston clogging through too rich mixes.

* Available only on CP512i and CP514i.







3-Step Easy Start – Hot or Cold

The electronic carburetor's electro-magnetic valve eliminates the standard choke and half throttle start.
Simply turn the saw on, and:

- 1. Push the primer 3x
- 2. Push decompression button
- 3. Pull the recoil



Multi- Stage Air Filtration

Patented twin-pipe interceptors create an air pulsation that draws fresh air in while pushing hot air away from the engine and releasing it out of the back to keep the saw running cool and reduce debris being trapped in the filter. The external rocker wheel vibrates the filter to further help release debris. This system extends filter life for less cleaning/replacement.



TECHNICAL DATA

MODEL	CP512 300	CP512 300 iLube [®]	CP514 350	CP514 350 iLube [®]		
Item No	701846 47558	701846 47560	701846 47562	701846 47564		
EAN 13 Code	5450248 563105	5450248 563112	5450248 563129	5450248 563136		
List Price Each (£)	1100.00	1200.00	1225.00	1325.00		
TECHNICAL DATA						
Power	4,0kW / 5,4HP	4,0kW / 5,4HP	4,0kW / 5,4HP	4,0kW / 5,4HP		
Max. blade x bore	Ø 300 x 20 / 25,4mm	Ø 300 x 20 / 25,4mm	Ø 350 x 20 / 25,4mm	Ø 350 x 20 / 25,4mm		
Max. cutting depth	100mm	100mm	125mm	125mm		
Rotation speed (RPM)	4450 min ⁻¹	4450 min ⁻¹	4450 min ⁻¹	4450 min ⁻¹		
Petrol + oil	≥ 92 RON +2%	≥ 92 RON + iLube [®] Automatic Mix	≥ 92 RON +2%	≥ 92 RON + iLube [®] Automatic Mix		
Water cooling	✓	✓	✓	✓		
Sound power / pressure level	108 dB (A) / 98 dB (A)	108 dB (A) / 98 dB (A)	108 dB (A) / 98 dB (A)	108 dB (A) / 98 dB (A)		
Dimensions	430 x 267 x 750mm	430 x 267 x 775mm	430 x 267 x 750mm	430 x 267 x 775mm		
Weight	10,1kg	10,2kg	10,4kg	10,5kg		

The Norton Clipper hand held cut-off saws are covered by a 6-month commercial warranty, from the date of sale.

Warranty conditions are detailed in the instruction manual.

