

CM42 COMPACT

FEATURES

- Wide conveyor cart, long reinforced frame.
- Ergonomic handle.
- Folding legs with repositionable tightening handle & transport wheels.
- Wide conveyor cart with tilted wheels, anti-pivoting and locking system.
- High accuracy cutting guide with per-degree angular setting.

BENEFITS

- Can cut a 60x60cm slab in two 30cm halves.
- Better comfort during use.
- Easy transportation and storage.
- Better stability and durability.
- Quick, precise and easy cut without additional accessory.



CM42



CM42 30-1-230V



CM42 30-1-110V

Item No.	70184647620	70184647989*	70184647990
Supply Voltage/ Power	230V 1~ / 2,2kW [3 Hp]	230V 1~ / 2,2kW [3 Hp]	110V 1~ / 1,5kW [2 Hp]
Fuse Generator	16A / 6 kVA	16A / 6 kVA	16A / 6 kVA
Blade x bore	Ø 400 x 25,4mm	Ø 400 x 25,4mm	Ø 400 x 25,4mm
Tool speed RPM	2800 min ⁻¹	2800 min ⁻¹	2800 min ⁻¹
Tilting table	Optional	Optional	Optional
Max. cutting depth	135mm	135mm	135mm
Max. cutting length	780mm	780mm	780mm
Max. material height	200mm	200mm	200mm
Table size	500 x 540mm	500 x 540mm	500 x 540mm
Hand Arm Vibrations	< 2,5 m/s ²	< 2,5 m/s ²	< 2,5 m/s ²
Sound power / pressure level	92 dB (A) / 80 dB (A)	92 dB (A) / 80 dB (A)	92 dB (A) / 80 dB (A)
Dimensions (LxWxH)	1187 x 620 x 1360mm	1187 x 620 x 1360mm	1187 x 620 x 1360mm
Dimensions (folded legs)	1187 x 620 x 740mm	1187 x 620 x 740mm	1187 x 620 x 740mm
Weight	90kg	90kg	90kg

* Available on request

PRODUCT FEATURES



MAX CUT DEPTH



FOLDING FEET



ADJUSTABLE CUTTING-DEPTH HANDLE



ANTI PIVOTING SYSTEM

DIAMOND BLADE RECOMMENDATIONS FOR CM42



Substrate / Material	BETON	SILENCIO	UNIVERSAL	ALL MATERIALS
Recommended Product	PRO BETON	EXTREME UNI SILENCIO	EXTREME UNIVERSAL	PRO 4X4 EXPLORER
Diameter x bore	400 x 25,4mm	400 x 25,4mm	400 x 25,4mm	400 x 25,4mm
Item No.	70184627062	70184640270	70184611438	70184602095
Page reference	67	36	37	48