


TR232 L

- Heavy duty guiding rail and tilting head facilitates precise cuts
- Built-in side extension accommodates large or wide materials
- Foldable handles, legs and transport wheels make moving and storing the machine simple
- The cutting table is easy to remove, which provides easy access to the water tray when cleaning
- Rubber coated table and clamps keep the cutting material steady and secure
- Ø 230mm Extreme Ceramic Turbo Diamond Blade supplied with every TR232 L



PRODUCT DATA

| | | | | | |
|----------|-------------|------------------------|---------------------|------------------------------------|------------------------|
| Item No. | 70184601103 | Supply Voltage / Power | 230V 1~ / 1.1kW | Max. cutting depth at 90° / at 45° | 15mm / 10mm |
| | | Fuse/Generator | 16A / 3 kVA | Max. cutting length | 1200mm |
| | | Blade x bore | Ø 230 x 25.4mm | Table size | 1200 x 565mm |
| | | Dimensions (LxWxH) | 1860 x 600 x 1175mm | Tool speed RPM | 2950 min ⁻¹ |
| | | Tilting head | 0 - 45° | Hand Arm Vibrations | < 2.5 m/s ² |
| | | Weight | 72kg | Sound power / pressure level | 71 dB (A) / 79 dB (A) |



PRODUCT FEATURES



ADJUSTABLE CLAMPS FOR FIXING THE TILES



ANGULAR CUTTING GUIDE / RUBBER-COVERED TABLE

DIAMOND BLADE WITH MACHINE FOR TR232 L



| | |
|----------------------|------------------------------|
| Substrate / Material | CERAMIC |
| Recommended Product | EXTREME CERAMIC TURBO |
| Blade x bore | 230 x 25.4mm |
| Item No. | 70184627653 |
| Page reference | 58 |