

# CPPG2.3 50Hz 1p 110V AVR



Genset image for illustration purposes only

## Technical data

Voltage	(V)	230 or 110
Frequency		50
Engine		CP200FA
Alternator		GA3000
Exhaust emission Level		EU2
Performance class		G1
Acoustic power LwA	dB(A)	95
Acoustic pressure LpA a 7 m	dB(A)	71

## Mechanical structure

Length (L)	(mm)	590
Width (W)	(mm)	430
Height (H)	(mm)	467
Weight	(kg)	52
Fuel tank capacity	(l)	15
Wheels and handles		NO

## Engine

### General

Engine Brand	CP
Engine Model	CP200FA
R.P.M.	3000
Power (C.V.)	2,5
Fuel	Petrol
No. of cylinders	1
Displacement	196
Bore (mm)	68
Stroke (mm)	54
Compression ratio	8.5:1
Regulation type	Mechanical
Exhaust emission Level	EU2

### Lubrication System

Oil capacity	0,6
Engine Oil Guard	Yes

### Air intake system

Air filter	Light duty
------------	------------

### Cooling System

Cooling type	Air
--------------	-----

### Starting system

Recoil	YES
Electric 12V	NO

## Power

Prime	Prime	Standby	Standby
kVA	kW	kVA	kW
2,3	2,3	2,5	2,5

## Fuel tank

Level sensor	YES
Fuel tank capacity	(l) 15

## Fuel consumption table

Load level	PRIME (L/h)	Aut. (h)
25%	-	-
50%	0,9	17,2
75%	1,3	11,3
100%	1,3	11,2
110%	-	-

NOTE: range according to the standard configuration.

## Alternator

Alternator brand	CP
Alternator Model	GA3000
Peak power 163°/27°	kVA 2,5
Poles	2
Excitation system	AVR
Performance at 100% p.f. 0.8 (%)	79

---

## Main features and options

### Mains features

- Recoil start
- Large fuel tank
- Automatic Voltage Regulation (AVR)
- Circuit breaker
- Sockets
- Engine Oil Guard
- Fuel Cock
- CE noise compliance
- Hourmeter

### Sockets configuration

SCHUKO 230V 16A IP54	1
UK 110V 16A IP44	1

### Options

## Regulations:

The generator set has a CE Marking that includes the following directives:

- 2006/42/CE Machine Safety.
- 2006/95/CEE Low Voltage.
- 2004/108/CE Electromagnetic compatibility.
- 97/68/CE Gases and contaminating particles emissions.
- 2005/88/CE Noise emission in the environment by equipment for use outdoors.

### Definitions

#### Prime Rating

PRIME POWER: Electrical power data available at a variable load without limits of hours per year. An overload of 10 % is allowed for 1 hour of every 12. In accordance with ISO 8528/1 (2005) – PRP

#### Standby

STANDBY POWER: Electrical power data at variable load in an emergency in accordance with standard ISO 8528/1 (2005) – ESP. Overloads of emergency power are not allowed.

#### Standard reference conditions

25 °C, 100 kPa and 30% relative humidity

Grupos Electrógenos Europa, S.A. is a certified company with ISO 9001, ISO 14001, OHSAS 18001 and PECAL

Chicago Pneumatic reserves the right to modify any characteristic of their equipment without prior warning.

All products are designed and engineered in Zaragoza Competence Center

Weight and dimensions of a standard generator set.

Non-contractual document

Chicago Pneumatic, S.A.  
Factory:  
Polígono pitarco II - Parcela 20  
50450 Muel (Zaragoza) España  
Tel.: +34 976 145 432  
Fax.: +34 976 145 431

DISTRIBUTED BY: